


## The first step for a smart factory begins with the warehouse



## ASRS AUTOMATED STORAGE AND RETRIEVAL SYSTEM

Since its launch in 1990, it's been highly rated by customers in various fields around the world.

### Manpower saving

Can be operated 24 hours a day, 365 days a year.  
Reduced Worker Burden.

### Space saving

We maximize the use of limited space and optimize the system footprint.


### Total Coordination

We offer comprehensive solutions based on our expertise as a system integrator, covering automated warehouses, AGVs, and control systems.


# Product Lineups

Customizable to suit your workpiece size and cycle time.

Single Type




Double Fork Type



Push-Pull Type



Dual Type



## Features

- Significant efficiency improvement in inbound and outbound operations
- Achieves high-precision inventory management for a wide variety of items
- Effective utilization of limited space
- Improved safety in the working environment
- Freely combinable with our production lines and AGVs

## Special Specifications

- Compliance with Overseas Standards
- Type with Fire Extinguishing Function
- Cleanroom Compatible
- High Temperature Resistant
- Predictive Maintenance

※Please consult us.

## Specification Table

Item	200kg type	1000kg type
Overall Height (m)	~8(18 <sup>*1</sup> )	~6 <sup>*2</sup>
Overall length (m)	~100	~100
Load configuration (m)	800~1500(L)×800~1500(W)×500~1500(H) <sup>*3</sup>	1300(L)×850~1300(W)×500~1500(H) <sup>*3</sup>
Load capacity (kg)	200	1,000
Maximum travel speed (m/min)	140(~200kg)、300(~150kg)	80
Lifting speed (m/min)	40(~200kg)、80(~150kg)	80
Maximum fork speed (m/min)	50	50
Drive method : traveling section	Servo	Inverter
Drive method : lifting section	Servo	Inverter
Drive method : fork section	Servo	Inverter

<sup>\*1</sup> Can accommodate up to a maximum of 18m, but with speed restrictions.

<sup>\*2</sup> Above 6m is subject to consultation.

<sup>\*3</sup> For anything not mentioned above, please consult us.

[Contact]

**Hirata**

Hirata Corporation Kanto Division

10-2 Hiraide Kogyodanchi, Utsunomiya, Tochigi, 321-0905 Japan TEL: <+81>(28)-661-3333 WEB: <http://www.hirata.co.jp/>



### Safety Precautions

- Complying with relevant laws and regulations and standards, and please take a risk prevention for safety.
- Read instruction manual carefully before use, and please surely use correctly.

● Information in this brochure is subject to change without notice. ● The pictures in this brochure are images, the actual product might be different.  
● All rights reserved.

20251030\_01